

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



The Delphion
Integrated
View

Other Views:
[INPADOC](#) | [Derwent...](#)

Title: **JP8306390A2: NONAQUEOUS ELECTROLYTE SECONDARY BATTERY**

Country: **JP Japan**
Kind: **A**

Inventor(s): **IKUYAMA SEIICHI
KOIKE TAKESHI**

Applicant/Assignee: **SONY CORP**
[News, Profiles, Stocks and More about this company](#)

Issued/Filed Dates: **Nov. 22, 1996 / April 28, 1995**

Application Number: **JP1995000106400**

IPC Class: **H01M 10/40; H01M 4/04; H01M 4/58; H01M 4/64;**

Priority Number(s): **April 28, 1995 JP1995000106400**


Abstract: **Purpose:** To improve resistance to overdischarge by coating nickel or chrome which has high chemical stability on copper foil at a specified thickness to be used as a negative electrode.
Constitution: On both surfaces of a negative electrode collector 9 having coating of nickel or chrome formed on copper foil in a plating method at a thickness of 1µm or more, synthetic paint of carbon or the like is applied to be a strip of a negative electrode 1. In the meanwhile, a positive electrode 2 is formed by applying mixed paint of LiCoO₂ or the like on both surfaces of a collector 10 of aluminum foil. The negative electrode 1, and the positive electrode 2 are laminated through a separator 3 to be a spiral electrode body. By thus coating the negative electrode 1 with thin film of nickel or chrome, it is passivated to improve chemical stability, thereby capacity deterioration by overdischarge can be restricted.
COPYRIGHT: (C)1996,JPO



Family: [Show known family members](#)

Other Abstract Info: none

Foreign References: No patents reference this one



[View Image](#)

1 pag



[Nominate this for the Gallery...](#)



(19)

(11) Publication number: **08306390 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **07106400**(51) Intl. Cl.: **H01M 10/40 H01M 4/04 H01M 4/58 H01M 4/64**(22) Application date: **28.04.95**

(30) Priority:

(43) Date of application
publication: **22.11.96**(84) Designated contracting
states:(71) Applicant: **SONY CORP**(72) Inventor: **IKUYAMA SEIICHI
KOIKE TAKESHI**

(74) Representative:

**(54) NONAQUEOUS
ELECTROLYTE
SECONDARY BATTERY**

(57) Abstract:

PURPOSE: To improve resistance to overdischarge by coating nickel or chrome which has high chemical stability on copper foil at a specified thickness to be used as a negative electrode.

CONSTITUTION: On both surfaces of a negative electrode collector 9 having coating of nickel or chrome formed on copper foil in a plating method at a thickness of 1 μ m or more, synthetic paint of carbon or the like is applied to be a strip of a negative electrode 1. In the meanwhile, a positive electrode 2 is formed by applying mixed paint of LiCoO₂ or the like on both surfaces of a collector 10 of aluminum foil. The negative electrode 1, and the positive electrode 2 are laminated through a separator 3 to be a spiral electrode body. By thus coating the negative electrode 1 with thin film of nickel or chrome, it is passivated to improve chemical stability, thereby

capacity deterioration by
overdischarge can be restricted.

COPYRIGHT: (C)1996,JPO

